

Polarshine 5

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Polarshine 5

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Polishing agent

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company	KWH Mirka Ltd Pensalavägen 210 66850 Jeppo / FINLAND Phone +358 20 760 2111 Fax +358 20 760 2290 Homepage www.mirka.com E-mail sales@mirka.com
---------	--

Address enquiries to

Technical information	sales@mirka.com
Safety Data Sheet	sdb@chemiebuero.de

1.4 Emergency telephone number

Company	+358 20 760 2111 (8:00 - 16:00)
---------	---------------------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flam. Liq. 4: H227 Combustible Liquid.
Eye Irrit. 2B: H320 Causes eye irritation.

2.2 Label elements

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200 (HCS 2012)

Hazard pictograms	none
Signal word	WARNING
Hazard statements	H227 Combustible Liquid. H320 Causes eye irritation.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from flames and hot surfaces.- No smoking. P370+P378 In case of fire: Use Water spray, Carbon dioxide, Foam, Dry chemical to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P264 Wash hands thoroughly after handling. P280 Wear protective gloves/eye protection. Call a POISON CENTER/doctor if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P501 Dispose of contents/container to in accordance with local/regional/national/international regulation.
Special labelling	Repeated exposure may cause skin dryness or cracking. Handling and processing operations should be conducted in accordance with 'best practices'.

Polarshine 5

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 2 / 8

2.3 Other hazards

Physico-chemical hazards	Combustible.
Human health dangers	Has a degreasing effect on the skin.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients**Product-type:**

The product is a mixture.

Range [%]	Substance
5 - < 10	Distillates (petroleum), hydrotreated light CAS: 64742-47-8 GHS/CLP: Flam. Liq. 4: H227 - Asp. Tox. 1: H304
5 - < 10	White mineral oil (petroleum) CAS: 8042-47-5 GHS/CLP: Asp. Tox. 1: H304

Comment on component parts For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General information	Change soaked clothing.
Inhalation	Ensure supply of fresh air.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Supply with medical care. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment neededTreat symptomatically.
Forward this sheet to the doctor.**SECTION 5: Fire-fighting measures****5.1 Extinguishing media**

Suitable extinguishing media	foam, dry powder, water spray jet, carbon dioxide
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixtureRisk of formation of toxic pyrolysis products.
Not combusted hydrocarbons.**5.3 Advice for firefighters**Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 3 / 8

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
High risk of slipping due to leakage/spillage of product.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Avoid spilling in enclosed areas.
Use solvent-resistant equipment.
During mechanical processing vacuuming at processing machines is necessary.
Keep away from all sources of ignition - Refrain from smoking.
Do not eat, drink or smoke when using this product.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.
Keep only in original container.
Do not store together with oxidizing agents.
Protect from heat/overheating.
Keep container in a well-ventilated place.
Keep container tightly closed.
Keep away from frost.
Prevent drying-out.

7.3 Specific end use(s)

See product use, SECTION 1.2

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 4 / 8

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UT)

Range [%]	Substance
5 - < 10	Distillates (petroleum), hydrotreated light CAS: 64742-47-8, EINECS/ELINCS: 265-149-8, EU-INDEX: 649-422-00-2 : 165 ppm, 1200 mg/m ³ , manufacture
5 - < 10	White mineral oil (petroleum) CAS: 8042-47-5, EINECS/ELINCS: 232-455-8, ECB-Nr.: 01-2119487078-27-XXXX : 5 mg/m ³ , TWA (as mist)

DNEL

Range [%]	Substance
5 - < 10	White mineral oil (petroleum), CAS: 8042-47-5 Industrial, inhalative, Long-term - systemic effects: 160 mg/m ³ . Industrial, dermal, Long-term - systemic effects: 220 mg/kg bw/d. general population, oral, Long-term - systemic effects: 40 mg/kg bw/d. general population, dermal, Long-term - systemic effects: 92 mg/kg bw/d. general population, inhalative, Long-term - systemic effects: 35 mg/m ³ .

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	Safety glasses.
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. In full contact: Butyl rubber, >480 min (EN 374). In splash contact Nitrile rubber, >480 min (EN 374).
Skin protection	Protective clothing. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier. Do not inhale dust. Do not inhale vapours. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of high concentrations. Short term: filter apparatus, combination filter A-P1.
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

Polarshine 5

**KWH Mirka Ltd
66850 Jeppo**

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 5 / 8

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	pasty
Color	white
Odor	mild
Odour threshold	not determined
pH-value	7,5 - 8,5
pH-value [1%]	not determined
Boiling point [°C]	not determined
Flash point [°C]	> 65 °C / >149 °F
Flammability [°C]	not determined
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	~1,05
Bulk density [kg/m ³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	>20,5 mm ² /s (40°C/ 104°F)
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not determined
Decomposition temperature [°C]	not determined

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with oxidizing agents.
Avoid drying up.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

See SECTION 10.3.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 6 / 8

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Range [%]	Substance
5 - < 10	White mineral oil (petroleum), CAS: 8042-47-5
	LD50, oral, Rat: > 5000 mg/kg.
	LD50, dermal, Rabbit: > 2000 mg/kg.
5 - < 10	Distillates (petroleum), hydrotreated light, CAS: 64742-47-8
	LD50, dermal, Rabbit: > 5000 mg/kg bw.
	LD50, oral, Rat: > 5000 mg/kg bw.
	LC50, inhalativ (vapour), Rat: > 5000 mg/m ³ .

Serious eye damage/irritation not determined**Skin corrosion/irritation** not determined**Respiratory or skin sensitisation** not determined**Specific target organ toxicity —
single exposure** not determined**Specific target organ toxicity —
repeated exposure** not determined**Mutagenicity** not determined**Reproduction toxicity** not determined**Carcinogenicity** not determined**General remarks** Frequent persistent contact with the skin can cause skin irritation.

Toxicological data of complete product are not available.

The product was classified on the basis of the calculation procedure of the preparation directive.

SECTION 12: Ecological information**12.1 Toxicity**

Range [%]	Substance
5 - < 10	Distillates (petroleum), hydrotreated light, CAS: 64742-47-8
	EL0, (48h), Daphnia magna: 1000 mg/l.
	EL0, (72h), Pseudokirchneriella subcapitata: 1000 mg/l.
	LL0, (96h), Oncorhynchus mykiss: 1000 mg/l.

12.2 Persistence and degradability**Behaviour in environment
compartments** not determined**Behaviour in sewage plant** not determined**Biological degradability** not determined**12.3 Bioaccumulative potential**

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment.

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 7 / 8

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	Dispose of as hazardous waste. Coordinate disposal with the authorities if necessary.
Contaminated packaging	Uncontaminated packaging may be taken for recycling. Packaging that cannot be cleaned should be disposed of as for product.
RCRA Hazard Class (40CFR 261)	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities.

SECTION 14: Transport

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

14.8 DOT Road Shipment Information (49 CFR) UN/NA NA1993 Combustible liquid, n.o.s.

Footnote: This material is not regulated under 49 CFR in a container of 119 gallon capacity or less when transported solely by land. Comb liq III

Polarshine 5

KWH Mirka Ltd
66850 Jeppo

Date printed 19.03.2015, Revision 12.02.2015

Version 01

Page 8 / 8

SECTION 15: Regulatory information

US Regulations

National regulations

- SARA, 302

29 CFR 1910.1200 (HCS 2012), OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA, TSCA, California - Prop. 65

This product is not classified as hazardous under SARA 302.

- SARA, 311

This product is not classified as hazardous under SARA 311.

- SARA, 313

This product contain one ingredient regulated under this list(40 CFR part 372.65): Aluminum oxide (fume or dust) (CAS 1344-28-1).

This product contain one ingredient regulated under this list(40 CFR part 372.65):

Cyclohexane (CAS 110-82-7)

- CA Proposition 65

No chemical substances in this material are named on the California P65 list.

- TSCA

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory.

- FDA

not determined

American Conference of Governmental Industrial Hygienists - ACGIH

Ingredients not listed as carcinogens.

International Agency for Research on Cancer IARC

Ingredients not listed as carcinogens.

National Toxicology Program - NTP

This product is named NTP - National Toxicology Program (contains cyclohexane).

HAP-VOC

ca. 9%

Transport-regulations

DOT-Classification, ADR (2013); IMDG-Code (2013, 36. Amdt.); IATA-DGR (2013).

Other Right to Know Laws

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H227 Combustible Liquid.

H304 May be fatal if swallowed and enters airways.

HMIS Ratings

HEALTH	1	1 - Slight Hazard
FLAMMABILITY	2	2 - Moderate Hazard
REACTIVITY	0	0 - Minimal Hazard
PERSONAL PROTECTION	X	X - Personal protection rating to be supplied by user depending on use conditions

NFPA Ratings

2
1 0
-

TOP, FLAMMABILITY: 2 - Moderate Hazard

LEFT, HEALTH: 1 - Slight Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard

BOTTOM, SPECIAL NOTICE: -

none

Key / Legende:

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstracts Service; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Products Regulations; DOT = Department of Transportation; EINCES = European Inventory of Existing Commercial Chemical Substances; EPA = Environmental Protection Agency; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit; TSCA = Toxic Substances Control Act

Copyright: Chemiebuero®